

# EVB300

Communication gateway for  
Envertech microinverters.



**FLEXIBILITY**  
Adapts to any system size  
and optimizes space.



**SMART**  
Module-level online smart  
monitoring.



**3 YEARS**  
Industrial leading warranty  
for monitoring devices.

Monitoring Device



Communicates with Envertech microinverters and enables users  
to manage the systems in a smart digital way.



**MIMOS**  
SERVICES



**ENVERTECH**

# DATASHEET

Model	EVB300
<b>Features</b>	
RS485 Port	Automatic Control of Power Output Virtual communication port, used for communication and control between RS485 equipment and EVB300.
Internet Connection Options	Ethernet/WIFI (802.11g/n)
Storage (Optional)	Standard USB Local Storage
<b>Capacity</b>	
Number of Devices Connected	Up to 60 Units MPPT per phase
<b>AC Supply / Consumption</b>	
AC Supply	108-264VAC, 47.5-62.5Hz
Power Consumption	<2W
<b>Mechanical Data</b>	
Dimensions (W*H*D)	182mm*100mm*43mm
Weight	345 g
Cooling	Natural Convection- No Fans
Ambient Temperature Range	-40 C ~+65 C
Ingress Protection (IP)	IP40
<b>Compliance&amp;Warranty</b>	
Compliance	CE
Warranty	3 Years

